

Haccess offers you the equipment of your bathroom, shower, mirrors, accessories, hairdryer and complements.

ORGANIC LED MIRROR H800 X W1200 MM BACKLIGHT & FRONTLIGHT, 4000° K, WITHOUT DEFOGGER



LED Organic mirror H800 x W1200 mm with backlight & frontlight lighting.
5 mm peripheral frosted border.
Green Mirox double-coat treatment.
Mirror thickness : 5 mm.
Colour temperature : 3000 K – neutral white.
LED strip 12V, IP65, 120 LEDs/m.
LED strip lifetime : 40 000 hours (guaranteed for 25,000 hours).
LED cooling through heat dissipation via an aluminium profile.
Luminous flux : 1200 lm/m.
CRI (Color Rendering Index) : 90.
Class 2, volume 2, IP44.
IP44 junction box.
Tension 230V | 50-60 Hz.
Supplied ready for installation, with mounting brackets and slotted holes for adjustment.
Option: 12 V with remote driver for installation within Zone 1 (accessible bathroom / PRM compliant).

Ref :
[LED.100.120.80.ORG.MIR.4.DEP](#)

TECHNICAL FEATURES

Dimensions

1200 x 800 mm

Materials

Glass

Haccess offers you the equipment of your bathroom, shower, mirrors, accessories, hairdryer and complements.

LED.100.120.80.ORG.MIR.4.DEP : ORGANIC LED MIRROR H800 X W1200 MM
BACKLIGHT & FRONTLIGHT, 4000° K, WITHOUT DEFOGGER

