

Haccess offers you the equipment of your bathroom, shower, mirrors, accessories, hairdryer and complements.

ORGANIC LED MIRROR H500 X W700 MM BACKLIGHT & FRONTLIGHT, 3000° K, WITH DEFOGGER



LED Organic mirror H500 x W700 mm with backlight & frontlight lighting.
5 mm peripheral frosted border.
Green Mirox double-coat treatment.
Mirror thickness : 5 mm.
Colour temperature : 3000 K – warm white.
LED strip 12V, IP65, 120 LEDs/m.
LED strip lifetime : 40 000 hours (guaranteed for 25,000 hours).
LED cooling through heat dissipation via an aluminium profile.
Luminous flux : 1200 lm/m.
CRI (Color Rendering Index) : 90.
Class 2, volume 2, IP44.
IP44 junction box.
Tension 230V | 50-60 Hz.
Supplied ready for installation, with mounting brackets and slotted holes for adjustment.
With defogger 30 W.
Option: 12 V with remote driver for installation within Zone 1 (accessible bathroom / PRM compliant).

Le miroir doit être raccordé à l'alimentation par l'intermédiaire d'un bloc de jonction classe 2 - IP24 conformément aux règles de la norme NFC 15-100 (non fourni).

Ref :
[LED.102.50.70.ORG.MIR.3.DEP](#)

TECHNICAL FEATURES

Dimensions

700 x 500 mm

Materials

Glass



Haccess offers you the equipment of your bathroom, shower, mirrors, accessories, hairdryer and complements.

Haccess offers you the equipment of your bathroom, shower, mirrors, accessories, hairdryer and complements.

LED.102.50.70.ORG.MIR.3.DEP : ORGANIC LED MIRROR H500 X W700 MM
BACKLIGHT & FRONTLIGHT, 3000° K, WITH DEFOGGER

