

Haccess offers you the equipment of your bathroom, shower, mirrors, accessories, hairdryer and complements.

ORGANIC LED MIRROR H600 X W1100 MM BACKLIGHT & FRONTLIGHT, 2700° K, WITH DEFOGGER



LED Organic mirror H600 x W1100 mm with backlight & frontlight lighting.

5 mm peripheral frosted border.

Green Mirox double-coat treatment.

Mirror thickness : 5 mm.

Colour temperature : 2700 K – extra warm white.

LED strip 12V, IP65, 120 LEDs/m.

LED strip lifetime : 40 000 hours (guaranteed for 25,000 hours).

LED cooling through heat dissipation via an aluminium profile.

Luminous flux : 1200 lm/m.

CRI (Color Rendering Index) : 90.

Class 2, volume 2, IP44.

IP44 junction box.

Tension 230V | 50-60 Hz.

Supplied ready for installation, with mounting brackets and slotted holes for adjustment.

With defogger 30 W.

Option: 12 V with remote driver for installation within Zone 1 (accessible bathroom / PRM compliant).

Le miroir doit être raccordé à l'alimentation par l'intermédiaire d'un bloc de jonction classe 2 - IP24 conformément aux règles de la norme NFC 15-100 (non fourni).

Ref :
LED.102.60.110.ORG.MIR.2.7.DEP

TECHNICAL FEATURES

Dimensions

1100 x 600 mm



Haccess offers you the equipment of your bathroom, shower, mirrors, accessories, hairdryer and complements.

Materials

Glass

Haccess offers you the equipment of your bathroom, shower, mirrors, accessories, hairdryer and complements.

LED.102.60.110.ORG.MIR.2.7.DEP : ORGANIC LED MIRROR H600 X W1100 MM
BACKLIGHT & FRONTLIGHT, 2700° K, WITH DEFOGGER

