

Haccess offers you the equipment of your bathroom, shower, mirrors, accessories, hairdryer and complements.

## ORGANIC LED MIRROR H600 X W900 MM BACKLIGHT, 3000° K, WITH DEFOGGER



LED Organic mirror H600 x W900 mm with backlight lighting.

Green Mirox double-coat treatment.

Mirror thickness : 5 mm.

Colour temperature : 3000 K – warm white.

LED strip 12V, IP65, 120 LEDs/m.

LED strip lifetime : 40 000 hours (guaranteed for 25,000 hours).

LED cooling through heat dissipation via an aluminium profile.

Luminous flux : 1200 lm/m.

CRI (Color Rendering Index) : 90.

Class 2, volume 2, IP44.

IP44 junction box.

Tension 230V | 50-60 Hz.

Supplied ready for installation, with mounting brackets and slotted holes for adjustment.

With defogger 30 W.

Option: 12 V with remote driver for installation within Zone 1 (accessible bathroom / PRM compliant).

**Le miroir doit être raccordé à l'alimentation par l'intermédiaire d'un bloc de jonction classe 2 - IP24 conformément aux règles de la norme NFC 15-100 (non fourni).**

Ref : LED.102.90.60.ORG.MIR.3

### TECHNICAL FEATURES

**Dimensions**

900 x 600 mm

**Materials**

Glass

Haccess offers you the equipment of your bathroom, shower, mirrors, accessories, hairdryer and complements.

LED.102.90.60.ORG.MIR.3 : ORGANIC LED MIRROR H600 X W900 MM  
BACKLIGHT, 3000° K, WITH DEFOGGER

